



V 1.2 - 072025

Elite 4K Premium Series 12X



This 12x Optical Zoom Camera, equipped with a 1/2.5" CMOS sensor and 8.51 megapixels, delivers 4K UHD resolution at 2160P30 with a wide 78° diagonal field of view. It supports advanced features like digital noise reduction, image flip, and precise PTZ control with 255 preset positions. The camera's integration capabilities include H.264/MJPEG video compression, multiple streaming protocols, PoE, HDMI, and USB connectivity. Its versatile use case spans conference rooms, educational settings, and live streaming applications. With excellent low-light performance, scalable pricing, and flexible configuration options, it is a comprehensive solution for modern video needs.

Key Features

- **12x Optical Zoom with 16x Digital Zoom** : Captures detailed images even at long distances, ideal for large conference rooms or lecture halls.
- **4K UHD Video Output** : Supports up to 2160P30 resolution, delivering crisp and clear visuals aligned with the trend for high-definition presentations.
- **Wide 78° Field of View** : Ensures better room coverage, reducing the need for multiple cameras.
- **Advanced Video Compression** : Utilizes H.264 and MJPEG to ensure seamless streaming even with varying network conditions.
- **Multi-Protocol Support (NDI, RTSP, Onvif)** : Enables flexible integration into various video systems, addressing recent demands for compatibility and interoperability in professional setups.

General Specifications

Camera

Sensor : 1/2.5 inches, CMOS, Effective Pixels 8.51

Megapixels

Lens : 12x, f4.4mm ~ 52.8mm, F1.8 ~ F2.6

Diagonal field of view : 78°

Video Format : YUY2 Max. 1080P30; MJPEG: Max. 2160P30; H.264 SVC/AVC: Max. 2160P30

Signal System : 4KP30, 4KP25, 1080P30, 1080P25

Scanning Mode : Progressive

Digital Zoom : 16X

Minimum Illumination : 0.5Lux @ (F1.8, AGC ON)

Shutter : 1/30 ~ 1/10000s

White Balance : Auto, Indoor, Outdoor, One Push, Manual VAR

Backlight Compensation : Support

Digital Noise Reduction : 2D & 3D Digital Noise Reduction

SNR : ≥ 55dB

Pan Angle : ± 170°

Tilt Angle : -30° ~ +90°

Pan Speed : 2.7° ~ 35.7° /s

Tilt Speed : 2.7° ~ 31.5° /s

Image Flip : Support

Preset Position : 255

Preset Accuracy : 0.1°

Network

Video Compression : H.264/MJPEG

Video Stream : First Stream, Second Stream

First Stream Resolution : 3840x2160, 1920x1080, 1280x720

Second Stream Resolution: 1920x1080, 1280x720, 1024x576

Video Bit Rate : 32kbps ~ 20480kbps

Bit Rate Control : VBR, CBR

Frame Rate : 50Hz 1fps ~ 25fps, 60Hz: 1fps ~ 30fps

Audio Compression : AAC

Audio Bit Rate : 96Kbps, 128Kbps, 256Kbps

Protocols : NDI@IHX2, TCP/IP, HTTP, RTSP, RTMP(s), Onvif, DHCP, SRT, GB/T 28181, Multicast.

USB

Operating System Supported : Windows 7 (only supports UVC1.1 features), Windows 8 and above versions, macOS 10.5 and above version, Linux 2.4.6 and above version, Android needs to include the version of UVC-related drivers

USB Video : Support

Color System / Compression : YUY2 / MJPEG / H.264

USB Video Communication Protocol : UVC 1.1 ~ 1.5

UVC PTZ Control : Support

General

USB Interfaces : 1x USB 3.0 Type-C

HD Output : 1x HDMI 1.4b

Network Interface : 1x RJ45 10M/100M/1000M adaptive Ethernet

Audio Interface : 1x LINE IN 3.5mm Jack

Control Interface : 1 x RS485 IN(Optional): 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA / Pelco-D / Pelco-P 1 x RS232 IN: 8pin Mini DIN, Max Distance: 30m, Protocol: VISCA / Pelco-D / Pelco-P.

Power Interface : JEITA Type (DC IN 12V)

Input Voltage : DC 12V / PoE (802.3af)

Input Current : 12V 1.0A (Max)

Operating Temperature : -10° C ~ 40° C

Storage Temperature : -40° C ~ 60° C

Power Consumption : 12W (Max)

Operating Humidity (RH): Up to 90%

General Specifications

Dimensions


Length (L) : 144 mm

Height (H) : 173.4 mm

Depth (D) : 144 mm

Net Weight : 1.41kg

Application Scenarios



Disclaimer:- Room setup diagrams are provided for reference only. Actual room setup and size may vary as per requirements.

Ordering Information

PeopleLink Elite 4K Premium Series 12X

:

PPU-PVC-EPS-12X-16DX

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers,
HITEC City, Hyderabad,
Telangana 500081, **India**
Phone: +91 9100123013
Email: vc@peoplelinkvc.com

International Contact Numbers

USA: +1 669-696-8383
Australia: +61 370 037070
France: +33 6 80 75 26 42
Middle East: +966 5300 19292
UK: +44 20 4571 5454

UAE: +971 4 3339082
Canada: +1 647-945-7373
Malaysia: +(6)018-2872188
New Zealand: +64-9-802-4666
Africa: +254 107 529 656

Tech Support

Toll Free: 1800 208 3399
customersupport@peoplelinkvc.com