



## PeopleLink Active LED - 6.67 Outdoor



Capture attention with the PeopleLink Active LED - 6.67 Outdoor , designed for eye-catching visuals in large spaces. It has a 6.67mm pixel pitch, which ensures excellent clarity for viewing distances over 6 meters and a high pixel density of 22,500 dots/m<sup>2</sup>.

With a brightness of at least 5000 cd/m<sup>2</sup> and a contrast ratio of 3000:1, it produces vibrant colors (adjustable from 3500K to 9300K) and deep blacks. The refresh rate of 1920Hz provides smooth motion for videos and graphics.

Its sturdy design is built to withstand the elements, with IP65 protection for the front and IP54 for the rear. This screen is perfect for digital billboards and large presentations, and it offers multiple connectivity options

## PeopleLink Active LED - 6.67 Outdoor

- 1 Seamless splicing, complete picture shown
- 2 Standardized module size, easy to install



- 3 Uniform and beautiful color with strong stereoscopic sense
- 4 High luminous intensity, the display content is clear when the sun irradiates directly on the screen

- 5 **100,000 hours lifespan, low maintenance cost**

## Active LED 6.67 Outdoor

### Parameters

|                              |   |                            |
|------------------------------|---|----------------------------|
| Pixel Pitch                  | : | 6.67mm                     |
| Pixel Configuration          | : | 1R1G1B                     |
| LED Type                     | : | SMD3535                    |
| Module Size                  | : | 320mm x 160mm              |
| Module Resolution            | : | 48 × 24 dots               |
| Colorful Evenness            | : | ≥97%                       |
| Cabinet Size                 | : | 960mm x 960mm x 140mm      |
| Cabinet Resolution           | : | 144 × 144 dots             |
| Cabinet Weight               | : | 46 ± 2 kg                  |
| Cabinet Material             | : | Iron                       |
| Pixel Density                | : | 22,500 dots/m <sup>2</sup> |
| Contrast Ratio               | : | 5000:1                     |
| Brightness                   | : | ≥5000                      |
| Color Temperature            | : | 3500K-9300K (adjustable)   |
| Viewing Angle                | : | H120°, V120°               |
| Recommended Viewing Distance | : | ≥6m                        |

### Technical Specs

|                       |   |                                          |
|-----------------------|---|------------------------------------------|
| Ingress Protection    | : | Front IP65 / Rear IP54                   |
| Rate Refresh          | : | 1920Hz                                   |
| Graylevel             | : | 16384                                    |
| Driving Mode          | : | Dynamic 1/6 scan, constant current drive |
| Input Voltage         | : | 200~240V AC                              |
| Input Power (max)     | : | 900W/m <sup>2</sup>                      |
| Input Power (typical) | : | 300W/m <sup>2</sup>                      |

|                              |   |                                                       |
|------------------------------|---|-------------------------------------------------------|
| <b>Lifespan</b>              | : | 100,000 h                                             |
| <b>Installation</b>          | : | Fixed                                                 |
| <b>Maintenance</b>           | : | Rear maintenance                                      |
| <b>Operating Temperature</b> | : | -20°C ~ +50°C                                         |
| <b>Operating Humidity</b>    | : | 10%RH ~ 65%RH (non-condensing)                        |
| <b>Signal Type</b>           | : | AV, S-Video, VGA, DVI, YPbPr, HDMI, SDI               |
| <b>Control Distance</b>      | : | CAT5 Cable (L < 100m)<br>Single mode fiber (L < 10km) |

## Ordering Information

### Part code

|                                                   |   |                  |
|---------------------------------------------------|---|------------------|
| PeopleLink Active LED - 6.67 Outdoor              | : | PDS-TP-32-T      |
| PeopleLink Active LED - 6.67 Outdoor Cabinet Unit | : | PPL-ALD-CU-OUTDR |

## SALES AND INQUIRIES

### Global Headquarters

Q3-A3, 10th Floor Cyber Towers,  
HITEC City, Hyderabad,  
Telangana 500081, **India**  
**Phone:** +91 9100123013  
**Email:** [vc@peoplelinkvc.com](mailto:vc@peoplelinkvc.com)

### International Contact Numbers

**USA:** +1 669-696-8383  
**Australia:** +61 370 037070  
**France:** +33 6 80 75 26 42  
**Middle East:** +966 5300 19292  
**UK:** +44 20 4571 5454  
**UAE:** +971 4 3339082  
**Canada:** +1 647-945-7373  
**Malaysia:** +(6)018-2872188  
**New Zealand:** +64-9-802-4666  
**Africa:** +254 107 529 656

### Tech Support

**Toll Free:** 1800 208 3399  
[customersupport@peoplelinkvc.com](mailto:customersupport@peoplelinkvc.com)

Follow us:       [www.peoplelinkvc.com/social-presence](http://www.peoplelinkvc.com/social-presence)

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (if any) are the property of their respective owners. Product images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.