



PeopleLink Video Mixer & Tracking Controller



Features

- 2 HDMI+ 4 HD/3G SDI input, 1+1 HDMI output.
- 6x1+1 seamless scaler switcher, maximum supported output resolution is 1080P@60Hz
- Seamless switching, no jitter, no blank screen.
- Adjustable image freezing function
- Web control function

Functions

- Turn on/off the channel number indicators
- 6x1 seamless scaler switcher, maximum supported output resolution is 1080P@60Hz,
- Seamless switching, no jitter, no blank screen.
- Adjustable image freezing function (freezing time from 1 to 6 seconds, freezing time cannot be less than 0.5 second or freezing function would be turned off).
- RS232 and Ethernet port to work with central controller or CLEACON series or CLASSIC-D series conference main unit for camera auto-tracking function

General Specifications

Interfaces

1x USB Out
2x HDMI input
4x SDI input
2x HDMI-A
1x female DP9 and 1x male DP9
1xRJ45 for Ethernet

Video Input

Signal format/Quantity : HDMIx2
Connector : HDMI-A connectors
Pixel bandwidth :165MHz
Protocol : HDMI 1.3a standard, HDCP1.3 protocol, DVI1.0 protocol
Support resolution :
1280x720@50Hz;1280x720@60Hz;
1920x1080@25Hz; 1920x1080@30Hz;
1920x1080@50Hz;1920x1080@60Hz
Transmission distance : less than 35m.
Signal format/Quantity : SDIx4
Connector : BNC female connectors
Pixel bandwidth :165MHz
Video format : Mbps SDI, 1.485Gbps HD-SDI and 2.97Gbps 3G-SDI
Support resolution : 1280x720@50Hz;1280x720@60Hz;
1920x1080@25Hz; 1920x1080@30Hz;
1920x1080@50Hz;1920x1080@60Hz
Transmission distance : 3G-SDI≤100m with certified SDI professional cable

Out Put

Signal format/Quantity : HDMIx2
Connector : HDMI-A connectors
Pixel bandwidth : 165MHz
Support resolution : 1280x720x50Hz;1280x720x60Hz;
1920x1080x50Hz;1920x1080x25Hz;
1920x1080x30Hz;1920x1080ix50Hz;
1920x1080x60Hz;1920x1080ix60Hz;
Transmission distance : HDMI≤7m with certified HDMI professional cable.

Control

RS232 control
Ethernet control
Front panel control

Mechanical

Dimensions (mm) : 483L x 260W x43.6D
Weight :3kg
Color : black

Ordering Information

Part code : **PL-CATC-B**

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers,
HITEC City, Hyderabad,
Telangana 500081, **India**
Phone: +91 9100123013
Email: vc@peoplelinkvc.com

International Contact Numbers

USA: +1 669-696-8383
Australia: +61 370 037070
France: +33 6 80 75 26 42
Middle East: +966 5300 19292
UK: +44 20 4571 5454

Tech Support

Toll Free: 1800 208 3399
customersupport@peoplelinkvc.com